arcosafetyjiTRANI70812-3060658

Prolonged contact (or immersion) | continous wear

Comfort and reinforced mechanical resistance for long-lasting chemical protection

SPECIFIC ADVANTAGES



Cut protection

A long cuff for a better protection of the forearm



Comfort

 Suitable for long-term wear; comfortable textile support, seamless working surfaces



Durability

• Optimised service life: high resistance to abrasion

safety.ir



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



CHEMICAL PROTECTION **TYPE A**

EN388

4122X

EN ISO 374-1 TYPE A



EN407



CAT.3

0334

DEXTERITY EN 420:

5/5

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Automotive assembly
- Machine tool manufacture
- Surface treatment
- Chemical product blending
- Cleaning tanks
- Handling and transporting drums of chemical products
- Manipulating valves
- Manufacture and application of paints and varnishes
- Unloading fuel
- Heavy-duty packaging



Chemical protection

arcosafety.iLTRANI79812-3969658

Prolonged contact (or immersion) | continous wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4 1 2 2 X

0-4 0-5 0-4 0-4 A-F P

Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance
Tear resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Blade cut resistance

Resistance to large quantities of molten metal

Resistance to small drops of molten metal

Radiant heat resistant
Convective heat resistance
Contact heat resistance
Burning behaviour

EN ISO 374-1 TYPE A



CHEMICAL RISKS

- A: Methanol
- J: n-Heptane
- K: Sodium hydroxide 40%
- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%

PRODUCT DETAILS

| Interior finish | Textile support |
|----------------------|-----------------|
| Exterior finish | Smooth |
| Material | Nitrile |
| Cuff characteristic | Feston Cuff |
| Colors of the gloves | Green |
| Length (cm) | 38 |
| Thickness (mm) | 1.30 |
| Size | 8 9 10 |

LOGISTIC DETAILS

| Packaging | 1 pair/bag 5 pairs/box |
|-----------|---------------------------|
| | 50 pairs/carton |

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/02/19/0480
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Edit 05/05/2021